



PORTABLE FIRE EXTINGUISHERS

80250 VERTICAL AUTOMATIC SPOT PROTECTION STORED PRESSURE

DESCRIPTION

Buckeye's Automatic Spot Protection Stored Pressure Fire Extinguishers are suitable for many local and total flood type applications.

They feature vertical mounting with optional horizontal and upright versions available.

These units are designed for individual hazard protection only.

*** These units are NOT intended for use in lieu of engineered systems and are not to be multiple mounted in larger than specified areas.***

FEATURES

- **Type Agent:** Multipurpose (ABC) Chemical
- **Operating Pressure** 100 PSI / 690 kPa Nitrogen
- **Vertical Mount**

SPECIFICATIONS

Buckeye's Model 80250 Vertical Automatic Spot Protection Stored Pressure Fire Extinguisher meets the following specifications.

- **Capacity:** 2.5 lbs / 1.13 kg
- **Full Unit Weight:** 4.5lbs. / 2.04 kg
- **Ship Weight:** 5 lbs / 2.27 kg
- **Length:** 15 ¼ in. / 38.7 cm
- **Diameter:** 3.4 in. / 8.6 cm
- **Operating Pressure:** 100 PSI / 690 kPa Nitrogen
- **Max. Total Flood Volume:** 120 cu. ft. / 3.4 cu. m
- **Total Flooding Max. Height Above Hazard:** 7 ½ ft. / 2.3 m
- **Local Application Coverage Area:** 4 x 4 ft. / 1.2 x 1.2 m
- **Local Application Max. Height Above Hazard:** 4 ft. / 1.2 m

ORDERING INFORMATION

80250 Vertical Automatic Spot Protection Multipurpose (ABC) Chemical:

Model Number 80250

Refer to the Buckeye spare parts list for replacement parts

