



PORTABLE FIRE EXTINGUISHERS

5 LB HALOTRON I STORED PRESSURE FIRE EXTINGUISHERS

DESCRIPTION

Buckeye's 5 LB Halotron I fire extinguisher is approved by the EPA and FAA as a HCFC blend B for use on "A", "B" and "C" type fires. This agent is an excellent replacement for Halon 1211.

It is ideal for computers, telephone switch gears, sensitive data storage areas, offices, boats, forest machines, aircraft flight lines and mobile units.

FEATURES

- Manufactured to ANSI/UL 1093 and ANSI/UL 711 standards.
- Marine / Vehicle Brackets Available.
- US Coast Guard Approved for Type B:C Size 1 Valid Only with Bracket No. A-6-H P/N 70027.
- Halotron I Available in 40 LB, 150 LB and 200 LB Cylinders for Recharging Buckeye Halotron I Extinguishers.

SPECIFICATIONS

Buckeye's 5 LB Halotron I Fire Extinguisher meets the following specifications:

- **Capacity:** 5 ½ lbs / 2.49 kg
- **U.L. Rating:** 5 B:C
- **Aluminum Valve**
- **Ship Weight:** 10 lbs / 4.5 kg
- **Height:** 16 ¾ in. / 41.6 cm
- **Width:** 6 9/16 in. / 16.7 cm
- **Diameter:** 4 ¼ in. / 10.8 cm
- **Range:** 9 -15 feet / 2.7-4.5 meters
- **Discharge Time:** 9 seconds
- **Cylinder:** Steel

ORDERING INFORMATION

5 LB Halotron I with Wall Hook:

P/N 75550

(Refer to the Buckeye spare parts list for replacement parts.)

