

**MODEL 50 AND 100
CARBON DIOXIDE
WHEELED EXTINGUISHERS
SELF CONTAINED PRESSURE**



MODEL 50



MODEL 100

SPECIAL FEATURES

- Universal 50 lb. and 100 lb. cart
- Balanced design for ease of handling
- Rugged steel tubing frame design
- Features wide wheel base (27") for stability
- Ability to be towed by vehicle
- Designed for one person operation
- The Model 100 is the only single cylinder 100lb. CO₂ extinguisher available.

CONSTRUCTION

- Built to ANSI/UL 154 and ANSI/UL 711 Standards
- Operating temperature range -40 Degrees F to 120 Degrees F (-40 Degrees C to 48.89 Degrees C)
- Brass chrome plated valves
- Powder-coated paint to withstand 240 hour salt spray test
- 16" full pneumatic rubber wheels
- Spun steel cylinders-3A-2015
- reinforced wire braided 1/2" inside diameter hose length per unit:
Model 50-15 ft. long
Model 100-40 ft. long

OPTIONAL FEATURES

- 16" steel wheels excellent on rugged and abusive surfaces in foundries and solvent environments
- 16" semipneumatic solid rubber wheels non-susceptable to flats.
- Tow ring-field added- provides positive means of vehicle towing: features military lunette eye connection

INDUSTRIAL USES

- Chemical Plants
- Manufacturing Plants
- Oil Rigs
- Rail Yards
- Warehouses
- Construction Sites
- Large Laboratories
- Parking Garages
- Airport Ramps
- Boat Docking

SPECIFICATIONS: PRODUCT

Model No.	Part No.	U.L. Rating	U.S.C.G. Type B:C Approved	Charge Weight	Height in/cm	Width in/cm	Depth in/cm	Discharge Range Ft/m	Discharge Time (sec.)	Shipping (Wt.LBS.)
50	35050	20B:C	SIZE IV	50 LB.	60/152.4	30/76.2	21/53.3	15/4.6	40 ± 5	250
100	35100	20B:C	SIZE V	100 LB.	65/165.1	30/76.2	21/53.3	15/4.6	80 ± 5	390