

**MODEL 350
PRESSURE TRANSFER & REGULATED
WHEELED FIRE EXTINGUISHERS**



SPECIFICATIONS

| Model Number | | A-350-RG | S-350-RG | K-350-RG | A-350-PT | S-350-PT | K-350-PT | |
|-----------------------------------|------------------|---------------------------|--------------|--------------|---------------------------|--------------|--------------|--|
| Part Number | | 32120 | 32220 | 32320 | 32110 | 32210 | 32310 | |
| Agent | | ABC | STD | PK | ABC | STD | PK | |
| UL Rating | | 40A:320B:C | 320B:C | 320B:C | 40A:320B:C | 320B:C | 320B:C | |
| Capacity | LBS. KG | 300 136.1 | 350 158.8 | 300 136.1 | 300 136.1 | 350 158.8 | 300 136.1 | |
| Shipping - WEIGHT | LBS. KG | 760 344.7 | 810 367.4 | 760 344.7 | 700 317.5 | 750 340.2 | 700 317.5 | |
| Discharge Time - SECONDS | | 53 | 59 | 56 | 57 | 50 | 84 | |
| Discharge Range | FT. M | 30-40 9.1 - 12.22 | | | 30-40 9.1 - 12.22 | | | |
| Nitrogen Cylinder Charge Pressure | PSI KPA | 2015 13903.50 | | | 2015 13903.50 | | | |
| Nitrogen Cylinder Size | CU. FT. LITRE | 220 6229.74 | | | 55 1557.43 | | | |
| Operation Temperature Range | °F °C | -65 to +120 -54 to +49 | | | -65 to +120 -54 to +49 | | | |
| Hose Length | FT. M | 50 15.2 | | | 50 15.2 | | | |
| Hose Diameter | IN. CM | 1 2.54 | | | 1 2.54 | | | |
| Wheels, Diameter | IN. CM | 36 x 6 91.44 x 15.24 | | | 36 x 6 91.44 x 15.24 | | | |
| Height | IN. CM | 58 147.32 | | | 58 147.32 | | | |
| Width | IN. CM | 36 91.44 | | | 36 91.44 | | | |
| Depth | IN. CM | 48 121.96 | | | 48 121.96 | | | |