



PORTABLE FIRE EXTINGUISHERS

2.5 F V/B HALOTRON I STORED PRESSURE FIRE EXTINGUISHERS

DESCRIPTION

Buckeye's 2.5 F V/B Halotron I fire extinguisher is approved by the EPA and FAA as a HCFC blend B for use on "A", "B" and "C" type fires. This agent is an excellent replacement for Halon 1211.

It is ideal for computers, telephone switch gears, sensitive data storage areas, offices, boats, forest machines, aircraft flight lines and mobile units.

FEATURES

- Manufactured to ANSI/UL 2129 and ANSI/UL 711 standards.
- Available with V/B bracket.

SPECIFICATIONS

Buckeye's 2.5 F V/B Halotron I Fire Extinguisher meets the following specifications:

- **Capacity:** 2 ½ lbs / 1.13 kg
- **U.L. Rating:** 2 B:C
- **Aluminum Valve**
- **Ship Weight:** 5 ½ lbs / 2.49 kg
- **Height:** 13 ¾ in. / 34.0 cm
- **Width:** 5 ⅝ in. / 14.3 cm
- **Diameter:** 3 ⅜ in. / 8.6 cm
- **Range:** 6 -10 feet / 1.8-3.0 meters
- **Discharge Time:** 9 seconds
- **Cylinder:** Steel

ORDERING INFORMATION

2.5 F V/B Halotron I Veh / Mar Bracket:
P/N 70251

Refer to the Buckeye spare parts list for replacement parts

